

AVON CODE 0778

# DOVER 50

PRODUCT # 1715

# MATERIAL SAFETY DATA SHEET

FORM SIMILAR TO FORM OSHA-20

## SECTION 2 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS	Use NA
(Method used)	Not needed
AVAILABILITY	CODE 0778
AVAILABILITY	TALC-DOVER 50
FIGHTING PROCEDURES	None
HAZARD	None
HAZARD	None

# H

## SECTION 3 - HEALTH HAZARD DATA

2 mg/M<sup>3</sup> (respirable dust)  
 LIMIT VALUE  
 No short term adverse effects expected  
 OVEREXPOSURE  
 Flush eyes with water  
 AND FIRST AID PROCEDURES

## SECTION 4 - REACTIVITY DATA

STABLE None  
 CONDITIONS TO AVOID  
 None  
 (Materials to avoid)  
 None  
 DECOMPOSITION PRODUCTS  
 WILL NOT OCCUR None  
 POLYMERIZATION CONDITIONS TO AVOID

## SECTION 5 - SPILL OR LEAK PROCEDURES

None  
 TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED  
 Not Applicable  
 TREATMENT METHOD

## SECTION 6 - SPECIAL PROTECTION INFORMATION

Use NIOSH approved dust respirator  
 PROTECTION (Specify type)  
 EXHAUST  MECHANICAL (General)  
 NONE  
 OTHER: None  
 VENTILATION  
 EYE PROTECTION OTHER:  
 EQUIPMENT

## SECTION 7 - SPECIAL PRECAUTIONS

Provide adequate ventilation  
 PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

As with all dusts, limit inhalation.

© TLV; 1984-1985

## DESCRIPTION

DOVER 50 is a high purity platy cosmetic talc made from Italian ore which is free of asbestos impurities, conforms to CTFA specifications and is specially treated to control bacteria.

The particle size of DOVER 50 is specially controlled in order to obtain a high loose and tapped density.

## CHEMICAL ANALYSIS

MgO	30%	Pb	not detected
SiO <sub>2</sub>	60	As	not detected
Al <sub>2</sub> O <sub>3</sub>	3		
CaO	1		
Fe <sub>2</sub> O <sub>3</sub>	0.5		

7 3/4 ± 2  
 7 1/2 ± 2  
 lbs./ft.<sup>3</sup> = 2  
 lbs./ft.<sup>3</sup> = 2  
 ± 0.5% max.  
 0.5%  
 ± 0.5

100%  
 98  
 62  
 30  
 20  
 12  
 8  
 17µm

Testing and are production.

Talc Division  
740-5440

# CYPRUS

1715-7-85

# CYPRUS

CMSDS-3-85

0780 4/87

CAS No. 14807-96-6

Section VIII - Special Protection Information

Eye Protection (use most appropriate)

Safety glasses, goggles, face shield

Skin Protection

Leather or rubber gloves.

Respiratory Protection

Use of dust respirator is recommended when exposure limits may be exceeded.

Ventilation

Local exhaust ventilation to collector or containment recommended to control dust to below exposure limits.

Section IX - Special Precautions

Good industrial hygiene practice requires that employee exposure be maintained below the recommended TLV. This is preferably achieved through the provision of adequate ventilation where necessary. Where dust cannot be controlled in this way, personal respiratory protection should be employed.

Issued: 12/02/85